



DSPA AEROSOL GENERATORS

DSPA 5-3 & 5-4



FEATURES:

- Exceptional effective non-toxic fire suppressing agent
- Does not deplete oxygen levels
- SNAP listing by EPA
- Ecologically safe and environmentally friendly (ODP=0, No GWP)
- Is harmless to humans and animals
- Does not cause any overpressure

Description

The DSPA 5-3 and DSPA 5-4 aerosol generators can be used by fire fighters and professional first responders as a highly effective knock down tool against fires. The DSPA 5-3/5-4 generators are non-pressurized and are deployed manually into a room or compartment that require firefighting. After activation, an aerosol cloud is generated, which expands volumetrically, flooding the space and knocking down the flames. The DSPA 5-3 and DSPA 5-4 generators are mainly designed to use on class A, B, C and F(K) fires.

Application

The DSPA 5-3 and DSPA 5-4 generators recommended for firefighting in buildings and other structures. They can be used in every fire stage, but their value is best displayed during fully developed fires.

Specifications

Model	5-3	5-4
Part Number	100006	100007
Dimensions	135 x 72 mm	165 x 94 mm
Total weight	1200 g	2200 g
Compound weight	300 g	900 g
Volume coverage	Up to 15 m ³	Up to 45 m ³
Discharge time	14-26 sec	19-31 sec
Activation, current	Manual Screw-in starter with pin or cord	Manual Screw-in starter with pin or cord
Operating conditions	-45°C to 75°C/ Up to 95% RH	-45°C to 75°C/ Up to 95% RH
Colour	Standard RAL 3000, other colours upon request	Standard RAL 3000, other colours upon request
Min. distance for persons (75°C) from discharge outlet		
Min. distance for combustible material (200°C) from discharge outlet		
Min. distance for construction structures (400°C) from discharge outlet		

More information:

DSPA.nl

Hogelandseweg 30

6545 AC Nijmegen

The Netherlands

T. +31 (0) 24 35 22 573

E info@dspa.nl

www.dspa.nl



Datasheet: DSPA GENERATOR

Serie: 5-3/5-4

Version: 2.3

Date: 24-07-2024